

**DECLARATION OF PERFORMANCE**

No. DoPS150-001

1. Unique identification code of the product-type :

**NDS 150**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4):

**Batch No. see packaging of the product**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**For use in drainage systems as filter, separation and drainage layer (F + S + D). EN 13252:2000 + A1:2005**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):

**Nophadrain BV  
Mercuriusstraat 10  
6468 ER KERKRADE, The Netherlands  
info@nophadrain.nl  
+31 (45) 5355030**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):

**not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 2+**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**Notified body No. 799 Kiwa MPA Bautest GmbH performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued the certificate of conformity of the factory production control  
No. 0799-CPD-26**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**not applicable**


9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Tensile strength (EN ISO 10319)	MD 8 kN/m (-1 kN/m) CMD 8 kN/m (-1 kN/m)	EN 13252:2000 + A1:2005
Static puncture (CBR test) (EN ISO 12236)	1,4 kN (-0,14 kN)	
Dynamic perforation resistance (cone drop test) (EN ISO 13433)	26 mm (+6,5 mm)	
Characteristic opening size (EN ISO 12956)	100 µm (+/- 30 µm)	
Water permeability normal to the plane (EN ISO 11058)	0,09 ms (-0,027 ms)	
Waterflow capacity in the plane (EN ISO 12958)	8,21 10 <sup>-3</sup> m <sup>2</sup> /s (-2,463 10 <sup>-3</sup> m <sup>2</sup> /s)	
Durability (EN 13252, annex B)	To be covered within 1 month Predicted to be durable for a minimum of 25 years in natural soils with 4 < pH < 9 and soil temperatures of < 25° C.	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of manufacturer by:

  
Mr. S.M. Droog (Director)